

SOLAR PUMP STATIONS WITH CONTROLLER

with el. socket to connect a heating element, switched by Ripple control



CSE SOL W SRS1 T-E HDO Pump Station

Pump Station with an integrated solar controller. The pump speed is controlled continuously by the controller and the flow rate through the solar thermal system is shown on its display. The pump station includes also a dedicated 230V power socket intended to connect an el. heating element of up to 3kW output. The power socket is switched by the controller depending on the storage tank temperature, time program and Ripple control.

TECHNICAL DATA

MAX. WORKING PRESSURE	6 bar
MAX. WORKING TEMPERATURE	110 °C
FLOW RATE MEASUREMENT RANGE	2-20 l/min
POWER SUPPLY	230 V, 50 Hz
HEATING ELEMENT SOCKET	230 V, max 3 kW
DIMENSIONS	470 x 265 x 120 mm


COMPONENTS

- Circulation pump PARA ST 25 / 7-50 / iPWM2
- 3m power cord with el. plug for controller & pump
- **Power cable for an el. heating element to connect to Ripple-controlled power supply**
- **SRS1T Controller with tank sensors connected (the assembly involves 1 solar sensor and 2 tank sensors)**
- **230V power socket intended to connect an el. heating element of up to 3kW output, switched by Ripple control and the controller**
- Check valve
- Safety valve
- Fill and drain valves
- Two ball valves
- Pressure gauge
- Thermometer
- Safety valve waste pipe
- Expansion vessel connection point
- Thermoinsulating case

MODELS

Connections	G 3/4" M	G 1" M	Cu 22mm	Cu 28mm
Code	17350	17349	17351	17352

DIAGRAM



ACCESSORIES

- ETT-N heating elements - see page 15
- Compression fitting adaptor for connecting a waste pipe to the safety valve:
Cu 22 x Cu 22 - **code 7629**
Cu 22 x 3/4" M - **code 13695**

