Regulus

www.regulus.eu

CSE TV ZV G70 3/4F HBOX

Installation and Operation Manual

CSE TV ZV G70 3/4F HBOX PUMP STATION

EN

CSE TV ZV G70 3/4F HBOX

1. Introduction

The kit is designed to ensure circulation in a distribution system of hot water heated by the RegulusHBOX indoor unit.

2. Description of the Kit with the Pump Station

The kit includes CSE TV ZV G70 3/4F pump station and brass parts for connection to the RegulusHBOX indoor unit. The pump station consists of a UPM3 DHW 15-70 pump including power cable, insulation, check valve, two ball valves and a thermometer.

The code of the kit is **20276**.

Data of Pump Station	
Fluid working temperature	5 - 95 °C
Max. working pressure	10 bar
Min. working pressure	0.5 bar
Ambient temperature	5 - 40 °C
Max. relative humidity	80 % non condensing
Power supply	230 V, 50 Hz
Insulation material	EPP RG 60 g/l
Overall dimensions	330 x 150 x 130 mm
Total weight	2.2 kg
Connections	2x G 3/4“F

3. Direction of Flow through the Pump Station

4. UPM3 DHW 15-70, 130 mm Pump

Design

A wet-running circulation pump, G 3/4“ M connection.

Electric Data	
Power supply	230 V, 50 Hz
Power input (min./max.)	2/52 W
Current (min./max.)	0.04/0.52 A
IP rating	IP44
Max. speed	5766 rpm
Weighted average power	≤ 23 W
Energy Efficiency Index	≤ 0.20 by EN 16 297/3
Motor protection	not needed

Pump control

The circulation pump can be controlled without a PWM signal by selecting the pump performance curve or using an external PWM control signal (profile for use in heating systems). A PWM pump control cable with connector is not included. It can be purchased as an optional accessory (code 16792), cable length 2 m.

The maximum operating curve of the pump can be defined.

- with no PWM signal the pump runs at max. speed following the selected curve
- with PWM signal the pump speed changes with the signal value up to the maximum of the selected curve

Performance curves



Curve	Max. H (upper graph)	Max. P_1 (lower graph)
1	5 mH_2O	33 W
2	6 mH_2O	39 W
3	7 mH_2O	52 W

Performance display

DISPLAY - LED MARKING

The LED numbering is further omitted for better clarity.

DISPLAY	PERFORMANCE CURVE	STATE	Max. H (upper graph)
	1	LOW PERFORMANCE	5 m
	2	MEDIUM PERFORMANCE	6 m
	3	HIGH PERFORMANCE	7 m

WARNING: LEDs may be mirrored, depending on the specific pump type.

GREEN LED FLASHING FREQUENCY	GREEN LED FLASHING FREQUENCY
1 flash per second	NO
12 flashes per second	YES

When switched on, the pump runs at factory settings or the last setting. The display shows the current pump performance.

Setting Selection for UPM3

To select your desired setting, press the button repeatedly until you find the setting you need (see the figure above). If you pass the desired setting, you have to go one more round until it appears again.

Error Display

DISPLAY	CONTROL MODE
	Seized pumpSeized pump
	Too low power supply voltage
	Electric fault

Prohibited positions

Permissible positions

Pump Wiring



socket for power supply (A)
and signal transmission (B)

power supply (A)
and signal (B) connectors

connector (B) with 2m cable is not
included in supply; it can be purchased as
optional accessory, code 16792

Connect the pump to the terminal block of the indoor unit. The specific terminal must be selected in the service interface of the regulator - see the instruction manual for the RegulusHBOX indoor unit.

5. How to Install the Kit on RegulusHBOX

1.

2.

3.

4.

5.

6.

7.

©2026 We reserve the right to errors, changes and improvements without prior notice.

REGULUS spol. s r.o.
E-mail: sales@regulus.eu
Web: www.regulus.eu