

THREAD SEALANTS

KOLGAS-UNI

Plastic sealing paste intended for both threaded and flanged connections, to be used with hemp. It is suitable for pipes with natural gas, hot and cold water, drinking water and steam. It remains soft and elastic and is absolutely non-toxic, prevents oxidation and features anti-corrosion effects.

Suitable for:

- use with hemp, mineral fibre gaskets, asbestos-free gaskets and rubber O-rings
- natural gas, hot and cold water, drinking water and steam

KOLGAS-UNI shall never be used for LPG and oxygen.



TECHNICAL DATA

CERTIFICATE	UNI - EN 751/2 A-Arp class approved by WRAS
COLOUR	green
PRESSURE RESISTANCE	gas: up to 0.5 MPa water and steam: up to 0.7 MPa
TEMPERATURE RESISTANCE	gas: - 35 to + 70 °C water and steam: - 35 to +130 °C

PACKAGING

Plastic container with lid 400g	Code - 10279
---------------------------------	--------------

HEMP

APPLICATION

Clean the thread and make it coarse. Wind hemp on the thread, apply the paste and screw in. The paste facilitates easy assembly, and thanks to its permanent elasticity, also easy dismantling.

PACKAGING

Bag, 1 000g	Code - 10289
-------------	--------------

