

CHEMICALS FOR DESCALING CIRCULATION PUMPS



NEUTRAL LIQUID

Neutralization solution designed for fast and safe neutralization of acid fluids in the process of heating systems cleaning and for descaling pump flushing.

Service life of descaling pumps is longer with this product.

TECHNICAL DATA

STATE	liquid
COLOUR	colourless
ODOUR	odourless
pH	11
DILUTION	3:100

APPLICATION

1. Having finished cleaning, drain the descaling pump into a plastic container suitable for transport of fluids and subsequently dispose of this fluid following the valid laws and local rules.
2. Fill the pump tank with an appropriate volume of clean water with respect to the volume of the system being cleaned, add 2-3% of Neutral Liquid and flush the system for at least 5 minutes.
3. As soon as flushing is finished* and all the fluid has returned to the pump tank, drain its contents into the same containers as the cleaning solution earlier.

PACKAGING

Plastic container, 10 kg

Code - 4006

* If you need to measure a pH value, use a litmus paper or an electronic pH meter (the recommended pH value is between 6 and 8.5).

DESCALING PUMPS

Pressure descaling pumps designed to remove sediments with the use of chemicals. Equipped with a 4-way valve, they facilitate cleaning solution flow reversal for the best cleaning results.



Manual pump



BOSS 5 FI



DOS 40 V4V



BOSS 22 FI