

PUMP STATIONS FOR HEATING CIRCUITS



CSE MIX W F Pump Station with electric mixing actuator

Pump station intended to control solid-fuel boiler flow to a mixed circuit or to a return line through an external controller.

Components

- Wilo circulation pump w. power cable
- Mixing valve w. female threaded connection
- Mixing valve actuator
- Neat insulation for reduced heat loss

Technical Data

FLUID WORKING TEMPERATURE	5 - 110 °C
MIXING VALVE ACTUATOR	3-point control, 120 s, 5 Nm
POWER SUPPLY	230 V, 50 Hz
IP RATING	IP44

Models

	CSE MIX W 1F	CSE MIX W PWM 1F	CSE MIX W 5/4F	CSE MIX PWM 5/4F
Connections	1" (3x F)	1" (3x F)	5/4" (3x F)	5/4" (3x F)
Pump	Yonos Para RS25/6	Yonos Para RS25/7,5-PWM	Yonos Para RS25/7,5	Yonos Para RS25/7,5-PWM
Max. head	6.2 m	7.6 m	7.6 m	7.6 m
K _{vs} of the valve	10 m ³ /h	10 m ³ /h	16 m ³ /h	16 m ³ /h
Code	16219	17281	16215	17282

Dimensions

