

PIPE INSULATION






Standard insulation



SOLARFLEX A-DUO Stainless Steel Pipes The insulation consists of sealed cells, without addition of PVC or substances dangerous to the ozone layer. It is soft and flexible. It withstands temperatures up to 175°C in long term, and up to 230°C in short term (stagnation).

Standard insulation	Insulation thickness	Code
DN _a 10	13 mm	6442
DN _a 13	13 mm	6443
DN _a 16	13 mm	6444
DN _a 18 by meter	13 mm	7426
DN _a 22 by meter	13 mm	7473
DN _a 28	13 mm	6447
DN _a 35	13 mm	7187
DN _a 15	19 mm	7053
DN _a 18 by meter	19 mm	7346
DN _a 18 self-adhesive, cut lengthwise	19 mm	7189
DN _a 22 by meter	19 mm	7347
DN _a 22 self-adhesive, cut lengthwise	19 mm	7190
DN _a 28 by meter	19 mm	12155
DN _a 28 self-adhesive, cut lengthwise	19 mm	9391
DN _a 35	19 mm	7188
DN _a 35 self-adhesive, cut lengthwise	19 mm	9392

ACCESSORIES

		CODE
	Aerotape insulation tape, 50 mm x 10 m - insulation 3 mm thick	6450
	Protape insulation tape, 50 mm x 25 m - insulation 0.6 mm thick	7252
	Flat sheet insulation, 1m wide, 13mm thick, 11m roll	7418
	Glue, 250 g, with a brush - 150°C	6452
	Glue, 1200 g - 150°C	19252