DATA SHEET

PS 700 N+ Thermal Store

Main Features	
Application	Storage and subsequent distribution of thermal energy from solid-fuel boilers, heat pumps or other heat sources.
Working fluid	water, water-glycol mixture (max. 1:1), water-glycerine mixture (max. 2:1), thermal oil
Thermal store code	15138
Insulation code	19316

Energy Efficiency Data (as per EC Regulation No. 812/2013)	
	valid for a thermal store with insulation
Energy efficiency class	N/A
Static loss	110 W
Storage volume	656 l

Technical data	
Total thermal store volume	656 l
Max. working temperature in thermal store	95 °C
Min. working temperature in thermal store	7 °C
Max. working pressure in thermal store	4 bar
Thermal store diameter	700 mm
Thermal store diameter with insulation	900 mm
Thermal store overall height	1955 mm
Tipping height without insulation	2080 mm
Thermal store perimeter insulation thickness	100 mm
Thermal store bottom insulation thickness	50 mm
Thermal store top insulation thickness	100 mm
Empty weight without insulation	84 kg

Materials	
Thermal store material	S235JR
Thermal store perimeter insulation	fleece
Thermal store outer surface insulation	hard polystyrene
Top and bottom thermal store insulation	fleece

Insulation thermal conductivity λ ≤ 0.037 W/mK, thermal resistance (short/long term) 150/100 °C, fire class E.

Accessories	
Electric heating element	ETT-A, C, D2, M, R, U, F2, P, S
Heating element max. length	755 mm

R E G U L U S spol. s r.o. Czech Republic
Do Koutů 1897/3, 143 00 Praha 4
Tel.: +420 241 764 506
Fax: +420 241 763 976
E-mail: sales@regulus.eu
Web: www.regulus.eu

DATA SHEET

PS 700 N+ Thermal Store

Dimensions



CONNECTIONS			
pos.	description	connection	height [mm]
Heat sources			
B1	Supply from heat source	G 6/4" F	1635
B2	Return to heat source	G 6/4" F	245
Heating system			
H1	Flow to heating system	G 6/4" F	1955
H2	Return from heating system	G 6/4" F	245
Control and safety			
C1	Temperature sensor	G 1" F	1635
C2	Temperature sensor	G 1/2" F	580
C3	Temperature sensor	G 1/2" F	1290
T	Thermometer	G 1/2" F	1505
P	Safety valve	G 1/2" F	450
Universal inlet/outlet			
U1	Universal inlet/outlet	G 6/4" F	1635
U2	Universal inlet/outlet	G 6/4" F	455
U3	Universal inlet/outlet	G 6/4" F	1175
U4	Universal inlet/outlet	G 6/4" F	705
U5	Universal inlet/outlet	G 6/4" F	1405

R E G U L U S spol. s r.o. Czech Republic
Do Koutů 1897/3, 143 00 Praha 4
Tel.: +420 241 764 506
Fax: +420 241 763 976
E-mail: sales@regulus.eu
Web: www.regulus.eu