PROTECTION AGAINST BOILER CORROSION AND FOULING
Load Units

RegulusRGMAT E R8 1“ KK
Load Unit with thermostatic mixing, with ball valves

RegulusRGMAT Load unit for solid-fuel boilers and fireplaces that **prevents low-temperature corrosion and boiler fouling by keeping a boiler (fireplace) inlet temperature** through a load valve.

The unit is completed with a set of three fittings with ball valves to facilitate the repair or disassembly of individual components without draining the system. RegulusRGMAT load unit comes in a left-hand version (outlet to boiler is on its left side), and can be easily modified to a right-hand version (outlet to boiler on its right side) during installation. Its installation position can be either horizontal or vertical.

TECHNICAL DATA

FLUID WORKING TEMPERATURE	**5–95 °C**
POWER SUPPLY	**230 V, 50 Hz**
IP RATING	**IP44**
TOTAL WEIGHT	**4.2 kg**
CONNECTIONS	**3x G 1“ F**
K_{vs} from A to AB	**7.3 m³/h**
K_{vs} from B to AB	**7.3 m³/h**
MAX. HEAD	**8.5 m**
PUMP OPERATING POINT at Δt 20 K	**2.4 m³/h flow rate 4.5 m head**
PUMP CONTROL	**ON/OFF (Δp-c / Δp-v / I, II, III)**

COMPONENTS

- Regulus RPA 25-8 high-efficiency circulation pump incl. connection cable
- 3 ball shutoff valves for inlets and outlet
- Thermometer
- Insulation
- TSV5BMF valve w. thermostatic element, opening temperature 55° or 65°C.

Prevention of low-temperature corrosion of boilers. Installation possible with A inlet from either right or left side. Minimum heat loss thanks to thermal insulation.

VERSIONS	CODE	VALVE OPENING TEMPERAT.	RECOMMENDED MAX. BOILER OUTPUT
RGMAT E 55 R8 1“ KK	21459	55 °C	53 kW
RGMAT E 65 R8 1“ KK	21460	65 °C	38 kW

CONNECTION IN A SYSTEM



DIMENSIONS