Regulus

CIRCULATION PUMP

Regulus RPC

High-efficiency ON/OFF circulation pump intended for DHW recirculation in domestic hot water piping. Thanks to its manual performance control, LED operation indicator and 3m cable with plug for socket, its settings and function checks are very easy.

- very quiet operation
- blockage-resistant motor
- manual performance control
- venting and manual restart functions
- ON/OFF control
- max. working pressure 10 bar
- 3m cable with plug for socket

High efficiency pump Regulus RPC

High-efficiency ON/OFF circulation pump intended for DHW recirculation in domestic hot water piping. Thanks to its manual performance control, LED operation indicator and 3m cable with plug for socket, its settings and function checks are very easy.

Technical Data

PORT-TO-PORT LENGTH	80 mm
CONNECTING THREAD	1/2“ F
HEAD	1.9 m
MAX. WORKING PRESSURE	10 bar
MAX. POWER INPUT	9 W
CODE	21685

Operating Modes

off

normal operation
speed setting (MIN–MAX)

air venting
5-minute cycle with alternating „off“ and „maximum speed“ modes

Pump station with RPC pump

CSE TV ZV RPC 1/2“
Pump station
for DHW recirculation

- 1/2“ F connection
- w. check valve, 2 ball valves
- insulation w. thermometer

CODE: 22105