

Regulus

Pump Stations

for heating systems



III ■
II ■
I ■
CP □
PP □

operating button

LED indication

NEW

with Regulus RPA 25-8
circulation pump

RegulusTOP Pump Stations

CSE2 Twin-line models



FOR UNMIXED HEATING CIRCUITS

- with filter & magnet
- connection: 1" F



FOR MIXED HEATING CIRCUITS

- with filter & magnet
- fitted with actuator/no actuator
- connection: 1" F
- with/without thermostatic mixing

CSE Single-line models



FOR UNMIXED HEATING CIRCUITS

- with/without filter & magnet
- with/without check valve
- connection: 1" F



FOR MIXED HEATING CIRCUITS

- fitted with actuator/no actuator
- connection: 1" F or 5/4" F

RegulusRGMAT Load Units

for solid-fuel boilers and fireplaces



- with thermostatic mixing (TSV valve included)
- valve opening temperature: 45-72 °C
- with automatic / manual bypass balancing
- models with ball valves with union nuts
- connection: 1" F or 5/4" F

Models available with a **range of circulation pumps**

- **Regulus** RPA 25-8
- **Wilo** PARA 25/6 SC
PARA 25/8 SC
PARA 25/8 iPWM
- **Grundfos** UPM3 AUTO 25-60
UPM3 FLEX AS 25-75

