


PS 700 K+ Thermal Store

	Main Features	
	Application	Storage and subsequent distribution of thermal energy from solid-fuel boilers, heat pumps or other heat sources.
	Working fluid	water, water-glycol mixture (max. 1:1), water-glycerine mixture (max. 2:1), thermal oil
	Thermal store code	15294
	Insulation code	19300

Energy Efficiency Data (as per EC Regulation No. 812/2013)	
	valid for a thermal store with insulation
Energy efficiency class	N/A
Static loss	116 W
Storage volume	737 l

Technical data	
Total thermal store volume	737 l
Max. working temperature in thermal store	95 °C
Min. working temperature in thermal store	7 °C
Max. working pressure in thermal store	4 bar
Thermal store diameter	790 mm
Thermal store diameter with insulation	990 mm
Thermal store overall height	1725 mm
Tipping height without insulation	1780 mm
Thermal store perimeter insulation thickness	100 mm
Thermal store bottom insulation thickness	50 mm
Thermal store top insulation thickness	100 mm
Empty weight without insulation	93 kg


Materials	
Thermal store material	S235JR
Thermal store perimeter insulation	fleece
Thermal store outer surface insulation	hard polystyrene
Top and bottom thermal store insulation	fleece

Insulation thermal conductivity $\lambda \leq 0.037$ W/mK, thermal resistance (short/long term) 150/100 °C, fire class E.

Accessories	
Electric heating element	ETT-A, C, D2, M, R, U, F2, P, S
Heating element max. length	815 mm

PS 700 K+ Thermal Store

Dimensions



CONNECTIONS

pos.	description	connection	height [mm]
Heat sources			
B1	Supply from heat source	G 6/4" F	1395
B2	Return to heat source	G 6/4" F	255
Heating system			
H1	Flow to heating system	G 6/4" F	1725
H2	Return from heating system	G 6/4" F	255
Control and safety			
C1	Temperature sensor	G 1/2" F	1395
C2	Temperature sensor	G 1/2" F	545
C3	Temperature sensor	G 1/2" F	1095
T	Thermometer	G 1/2" F	1275
P	Safety valve	G 1/2" F	425
Universal inlet/outlet			
U1	Universal inlet/outlet	G 6/4" F	1395
U2	Universal inlet/outlet	G 6/4" F	445
U3	Universal inlet/outlet	G 6/4" F	1015
U4	Universal inlet/outlet	G 6/4" F	635
U5	Universal inlet/outlet	G 6/4" F	1175