


DATA SHEET
PS2F 1000 N+ Thermal Store

	Main Features	
	Application	Storage and subsequent distribution of thermal energy from solid-fuel boilers, heat pumps or other heat sources; the tank is fitted with 2 flanged openings that can permit installation of a DHW tube heat exchanger or connecting a solar thermal system
	Working fluid	water, water-glycol mixture (max. 1:1), water-glycerine mixture (max. 2:1), thermal oil
	Storage tank code	15221
	Insulation code	19340

Energy Efficiency Data (as per EC Regulation No. 812/2013)	
	valid for a tank with insulation
Energy efficiency class	N/A
Static loss	141 W
Storage volume	932 l

Technical data	
Total storage tank volume	932 l
Max. working temperature in storage tank	95 °C
Max. working pressure in storage tank	4 bar
Storage tank diameter	800 mm
Storage tank diameter with insulation	1000 mm
Storage tank overall height	2080 mm
Tipping height without insulation	2120 mm
Storage tank perimeter insulation thickness	100 mm
Storage tank bottom insulation thickness	50 mm
Storage tank top insulation thickness	100 mm
Empty weight without insulation	116 kg

Materials	
Storage tank material	S235JR
Storage tank perimeter insulation	fleece
Storage tank outer surface insulation	hard polystyrene
Top and bottom storage tank insulation	fleece

PS2F 1000 N+ Thermal Store

Accessories	
Electrical heating element	ETT-A, C, D, F, P, M
Heating element max. length	815 mm
Blind flange	code 6230
Blind flange for heat exchanger	code 6231 / 6232
Tube heat exchanger	max. area 4.5 m ²

Dimensions																																																																																								
	TAPPINGS																																																																																							
	<table border="1"> <thead> <tr> <th>pos.</th> <th>description</th> <th>connection</th> <th>height [mm]</th> </tr> </thead> <tbody> <tr> <td colspan="4">Heat sources</td> </tr> <tr> <td>B1</td> <td>Supply from heat source</td> <td>G 6/4" F</td> <td>1690</td> </tr> <tr> <td>B2</td> <td>Return to heat source</td> <td>G 6/4" F</td> <td>300</td> </tr> <tr> <td colspan="4">Heating system</td> </tr> <tr> <td>H1</td> <td>Supply to heat sink</td> <td>G 6/4" F</td> <td>2080</td> </tr> <tr> <td>H2</td> <td>Return from heat sink</td> <td>G 6/4" F</td> <td>300</td> </tr> <tr> <td colspan="4">Control and safety</td> </tr> <tr> <td>C1</td> <td>Temperature sensor</td> <td>G 1/2" F</td> <td>1705</td> </tr> <tr> <td>C2</td> <td>Temperature sensor</td> <td>G 1/2" F</td> <td>635</td> </tr> <tr> <td>C3</td> <td>Temperature sensor</td> <td>G 1/2" F</td> <td>1345</td> </tr> <tr> <td>T</td> <td>Thermometer</td> <td>G 1/2" F</td> <td>1475</td> </tr> <tr> <td>P</td> <td>Safety valve</td> <td>G 1/2" F</td> <td>525</td> </tr> <tr> <td colspan="4">Universal inlet/outlet</td> </tr> <tr> <td>U1</td> <td>Universal inlet/outlet</td> <td>G 6/4" F</td> <td>1690</td> </tr> <tr> <td>U2</td> <td>Universal inlet/outlet</td> <td>G 6/4" F</td> <td>510</td> </tr> <tr> <td>U3</td> <td>Universal inlet/outlet</td> <td>G 6/4" F</td> <td>1230</td> </tr> <tr> <td>U4</td> <td>Universal inlet/outlet</td> <td>G 6/4" F</td> <td>760</td> </tr> <tr> <td>U5</td> <td>Universal inlet/outlet</td> <td>G 6/4" F</td> <td>1460</td> </tr> <tr> <td colspan="4">Flanges</td> </tr> <tr> <td>L1</td> <td>Upper flange</td> <td>12 x M12</td> <td>1590</td> </tr> <tr> <td>L2</td> <td>Lower flange</td> <td>12 x M12</td> <td>410</td> </tr> </tbody> </table>	pos.	description	connection	height [mm]	Heat sources				B1	Supply from heat source	G 6/4" F	1690	B2	Return to heat source	G 6/4" F	300	Heating system				H1	Supply to heat sink	G 6/4" F	2080	H2	Return from heat sink	G 6/4" F	300	Control and safety				C1	Temperature sensor	G 1/2" F	1705	C2	Temperature sensor	G 1/2" F	635	C3	Temperature sensor	G 1/2" F	1345	T	Thermometer	G 1/2" F	1475	P	Safety valve	G 1/2" F	525	Universal inlet/outlet				U1	Universal inlet/outlet	G 6/4" F	1690	U2	Universal inlet/outlet	G 6/4" F	510	U3	Universal inlet/outlet	G 6/4" F	1230	U4	Universal inlet/outlet	G 6/4" F	760	U5	Universal inlet/outlet	G 6/4" F	1460	Flanges				L1	Upper flange	12 x M12	1590	L2	Lower flange	12 x M12
pos.	description	connection	height [mm]																																																																																					
Heat sources																																																																																								
B1	Supply from heat source	G 6/4" F	1690																																																																																					
B2	Return to heat source	G 6/4" F	300																																																																																					
Heating system																																																																																								
H1	Supply to heat sink	G 6/4" F	2080																																																																																					
H2	Return from heat sink	G 6/4" F	300																																																																																					
Control and safety																																																																																								
C1	Temperature sensor	G 1/2" F	1705																																																																																					
C2	Temperature sensor	G 1/2" F	635																																																																																					
C3	Temperature sensor	G 1/2" F	1345																																																																																					
T	Thermometer	G 1/2" F	1475																																																																																					
P	Safety valve	G 1/2" F	525																																																																																					
Universal inlet/outlet																																																																																								
U1	Universal inlet/outlet	G 6/4" F	1690																																																																																					
U2	Universal inlet/outlet	G 6/4" F	510																																																																																					
U3	Universal inlet/outlet	G 6/4" F	1230																																																																																					
U4	Universal inlet/outlet	G 6/4" F	760																																																																																					
U5	Universal inlet/outlet	G 6/4" F	1460																																																																																					
Flanges																																																																																								
L1	Upper flange	12 x M12	1590																																																																																					
L2	Lower flange	12 x M12	410																																																																																					